

INSIGHT-S285(2.8MM) - TP-LINK VIGI 8MP FULL-COLOR Cámara domo de red



SKU: INSIGHT-S285(2.8MM)

Link: <https://www.mundicam.com/productos/video-ip/camaras-ip/ip-domos-fijos/insight-s2852-8mm/>

PRODUCT INFORMATION

Marcas: 3191

Categorías: VIDEO IP HD, Cámaras IP, Cámaras IP Minidomo

Etiquetas: TPLINK, VIGI

Súper alta definición de 8MP (4K) y 24 horas a todo color
Análisis de personas y vehículos
Clasificación de personas y vehículos
Detección inteligente
Tecnología de mejora de vídeo inteligente
Defensa activa y audio bidireccional
Resistente al agua
IP67
Tecnología de compresión H.265+

ESPECIFICACIONES TÉCNICAS

Cámara

LENS

Sensor de Imagen	1/2.7" Progressive Scan CMOS
Shutter Speed	1/3 to 1/10000 s
Slow Shutter	Yes
Iluminación Mínima	0.005 Lux; 0 Lux with IR/White light
Mecanismo Día/Noche	IR Cut Filter
Day/Night Switch	Unified/ Scheduled/ Auto

Cámara

LENS

Type	Fixed Focal Lens
Focal Length	2.8 mm / 4 mm
Aperture	F1.6
FOV	• 2.8 mm: Horizontal FOV: 110°, Vertical FOV: 58.1°, Diagonal FOV: 133.5° • 4 mm: Horizontal FOV: 88°, Vertical FOV: 46°, Diagonal FOV: 105.4°
Lens Mount	M12*P 0.5
DORI Distance	• 2.8 mm Detect: 85 m (278 ft) Observe: 35 m (116 ft)

Cámara	
LENS	
	Recognize: 17 m (56 ft) Identify: 8 m (28 ft)
	• 4 mm Detect: 107 m (350 ft) Observe: 44 m (146 ft) Recognize: 21 m (70 ft) Identify: 11 m (35 ft)
Angle Adjustment (Manual)	
ILLUMINATOR	
Range	Pan: 0° to 346°, Tilt: 0° to 75°, Rotation: 0° to 355°
Angle Adjustment (Manual)	
ILLUMINATOR	
IR LED	• Quantity: 2 • Range: 30m • Wavelength: 850nm • Quantity: 2 • Range: 30m Auto/Scheduled/Always on/Always off
White LED	
Illuminator On/Off Control	
VIDEO	
Image	
Max. Resolution	3840 x 2160
Main Stream	• Frame Rate? 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
	• Resolution: 3840x2160, 2560x1440, 2304x1296, 2048x1280, 1920x1080, 1280x720
	• Note: If the image rotation is set to 90° or 270°, the frame rate only supports 10fps. If HDR is turned on, the frame rate can only support up to 20fps.
Sub-Stream	• Frame Rate? 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
	• Resolution: 848x480, 704x576, 640x480, 640x360, 352x288, 320x240
	• Note: If the image rotation is set to 90° or 270°, the frame rate only supports 10fps. If HDR is turned on, the frame rate can only support up to 20fps.
Bit Rate Control	CBR, VBR
Compresión de video	• Main Stream: H.265+/H.265/H.264+/H.264 • Sub-Stream: H.265/H.264
H.264 Type	High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile
H.265+	Main Stream Supported
Video Bit Rate	• Main Stream: 256 Kbps to 8 Mbps • Sub-Stream: 64 Kbps to 512 Kbps
VIDEO	
Image	
Image Settings	• Mirror • Brightness • Contrast • Saturation • Sharpness

VIDEO	
Image	
	• Exposure • WDR • White Balance • Prevent Overexposure to Infrared Light • HLC Adjustable by Client Software
Image Enhancement	BLC/3D DNR/HLC/Smart IR
Wide Dynamic Range	120 dB
	Note: When People & Vehicle Analytics is enabled, only DWDR is supported
SNR	≥ 52 dB
Image Parameters Switch	Yes
Privacy Mask	Up to 4 Masks
ROI	1 Region
OSD Setting	Yes
AUDIO	
Red	
Comunicación de Audio	Two-Way Audio
Entrada de Audio	Yes
Salida de Audio	Yes
Compresión de Audio	Yes
Audio Sampling Rate	8KHz
Environment Noise Filtering	Yes
Audio Bit Rate	64 Kbps(G.711 alaw)
AUDIO	
Red	
Protocolo	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP
ONVIF	Yes
API	Open Network Video Interface (Profile S/T/G)
Vista en vivo simultánea	3 Main Streams & 3 Sub-Streams
Client	VIGI App, Web UI, VIGI VMS, Utility
Web Browser	• Google Chrome® 57 and above • Firefox® 52 and above • Safari® 11 and above • Microsoft® Edge 91 and above
Cloud	Yes
Seguridad	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
ALARMA Y GESTIÓN DE EVENTOS	
Deep Learning Function	
Smart Event	• Intrusion Detection • Line-Crossing Detection • Region Entering Detection • Region Exiting Detection • Object Abandoned Detection • Object Removal Detection • Loitering Detection • People Detection • Vehicle Detection • Abnormal Sound Detection • Scene Change Detection
Basic Event	• Motion detection(Enhanced with Human & Vehicle Classification for • Camera Tampering • Exception (Illegal Login) • Memory Card Video Recording • Message Push • Audible Warning • White Light Flashing
Alarm Linkage	
ALARMA Y GESTIÓN DE EVENTOS	
Deep Learning Function	

ALARMA Y GESTIÓN DE EVENTOS

Deep Learning Function

People & Vehicle Analytics

INTERFACES

GENERAL

Interfaz de Red

Alarma

Reset Button

Power

Almacenamiento interno

Built-in Microphone

Built-in Speaker

Audio

INTERFACES

GENERAL

Temperatura de funcionamiento

Storage Temperature

Humedad de funcionamiento

Storage Humidity

Contenido del Paquete

Material

Peso neto

Power Supply

Protection

Product Dimensions (L x W x H)

Certificaciones

Search and filter to people or vehicle of interest based on many different

1 RJ45 10/100M Self-Adaptive Ethernet Port, PoE

N/A

Yes

DC Power Port

Built-In Memory Card Slot, Support MicroSD Card, up to 512 GB^s

Yes; Records Anything Going on within a 16.4-ft (5 m) Radius of the C

Yes

N/A

-30–60 °C

-40–60 °C

95% or Less (Non-Condensing)

95% or Less (Non-Condensing)

- VIGI Network Camera
- Quick Start Guide
- Waterproof Cable Attachments
- Mounting Accessories

Metal

0.62 Kg

• 12V DC ± 5%, Max. 11 W, 5.5 mm Coaxial Power Plug

• PoE: 802.3af/at, class 0, Max. 12.3 W

IP67 Waterproof, IK10 Vandal Proof

4.80 × 4.80 × 3.50 in (122 × 122 × 89 mm)

CE, NTRA, FCC, VCCI, BSMI, ONVIF, KC