

SD-H2C - Cubo PT IP H265 2M DN IR10m 4mm Wifi Audio SD 5V MIC



SKU: SD-H2C

Link: <https://www.mundicam.com/productos/video-ip/camaras-ip/ip-cubo/sd-h2c/>

PRODUCT INFORMATION

Marcas: 2338

Conmutación: 1956

Lente: 1980

Categorías: VIDEO IP HD, Cámaras IP, IP Consumo

Etiquetas: DAHUA

Resolución hasta 2MP@25IPS. Óptica fija de 4mm (85.9°x44.9°x103.3° (HxVxD)), F2.0. WiFi: IEEE802.11b/g/n 2.4-2.4835GHz, 2.4G. Visión nocturna, imágenes nítidas incluso de noche. Distancia de iluminación hasta 15m (IR). Protección de la intimidad en un solo clic. Admite tarjeta micro SD hasta 512G (no incluida). Visión de 360° sin ángulos muertos (Pan: 0° a 325°; Tilt: -20° a +100°). Seguimiento automático de objetivos (Auto Tracking). Detección de personas (Human Detection). Dispone de audio bidireccional. Micrófono y altavoz incorporados. Fácil de usar con la APP DMSS. Material de la carcasa: plástico. Alimentación / Consumo: 5Vdc@1A (2W, máx 5W). Alimentador incluido. Dimensiones y peso: Ø95.5x130.4mm / 0.250Kg. Serie Hero.

ESPECIFICACIONES TÉCNICAS

Camera	
Image Sensor	1/2.8" CMOS
Max. Resolution	1920 (H) × 1080 (V)
Electronic Shutter Speed	Auto/Manual 1/3s~1/100000s
Illumination Distance	15m(49.21 ft)
Illuminator On/Off Control	Manual; Auto; Off
Illuminator Number	1 (IR light)
Angle Adjustment	Pan: 0° to 325° Tilt: -20° to +100°
Max. Aperture	F2.0
Field of View	H: 85.9°; V: 44.9°; D: 103.3°
Intelligence	

Human Detection	Yes
Video & Audio	
Video Compression	H.264B;Smart H.265+;H.264;H.265;Smart H.264+;MJPEG
Resolution	1080p (1920×1080); (1.3M)1280×960; 720p (1280×720)
Video Frame Rate	Main stream: 1080p/1.3M/720p(1–25/30fps) Sub stream 1: D1/CIF(1–25/30fps)
Video Bit Rate	H.264: 256 Kbps–8192 Kbps H.265: 144 Kbps–8192 Kbps
Day/Night	Auto(ICR)/Color/B/W
WDR	DWDR
Motion Detection	Support
Image Rotation	180°
Built-in MIC	Yes
Built-in Speaker	Yes
Audio Compression	PCM; G.711a; G.711Mu; G.726; MPEG2-Layer2; G722.1
Network	
Network Port	RJ-45 (10/100 Base-T)
Wi-Fi	IEEE 802.11b/g/n 2.412-2.472 GHz, 2.4 G
Power Transmission	?20 dBm@2400–2483.5 MHz
Storage	FTP; Micro SD card (512 GB)
Management Software	DMSS
Mobile Client	iOS;Android
General	
Certifications	CE
Power Supply	5 VDC, 1 A ± 10% (Type-C)
Power Consumption	Basic: 2 W Max: 5 W (illuminator +PTZ +speaker)
Operating Conditions	–10 °C to +40 °C (14 °F to +104 °F)
Operating Humidity	? 95%
Casing Material	Plastic
Product Dimensions	130.4mm×?95.5mm
Net Weight	0.25 kg (0.55 lb)